

The following Listing of Claims will replace all prior versions, and listings, of claims in the application.

**LISTING OF CLAIMS:**

1. (Cancelled)
2. (Cancelled)
3. (Cancelled)
4. (Cancelled)
5. (Currently Amended) An air conditioner updating method comprising:  
recovering a working refrigerant containing an existing refrigerant oil from an existing air conditioner;  
updating selected equipment constituting at least a portion of the existing air conditioner while ~~leaving~~ reusing as is at least a portion of existing refrigerant piping of the existing air conditioner when updating the air conditioner is complete, the existing refrigerant piping being connected a heat source unit and a user unit;  
charging the existing air conditioner that has the equipment updated with a new working refrigerant that serves as a cleaning agent comprising an HFC refrigerant containing at least 40 wt% of R32 but containing no R134a refrigerant; and  
washing the existing refrigerant piping of the existing air conditioner that used the existing refrigerant oil by circulating the new working refrigerant such that the existing refrigerant oil remaining in the existing refrigerant piping is carried along with the new working refrigerant during the circulating of the new working refrigerant, and separating the existing refrigerant oil from the working refrigerant in order to remove the existing refrigerant oil from the existing refrigerant piping.

6. (Previously Presented) The air conditioner updating method recited in claim 5, wherein

during the washing of the existing refrigerant piping, the new working refrigerant is circulated such that the new working refrigerant in a wet state flows through the existing refrigerant piping.

7. (Currently Amended) A refurbished air conditioner comprising:  
existing refrigerant piping that was used with an existing air conditioner and contains residue of an existing refrigerant oil, the existing refrigerant piping being connected a heat source unit and a user unit, the existing refrigerant piping being reused as is when updating the air conditioner is complete;

a heat source unit and a user unit that are connected together by the existing refrigerant piping with a replaced working refrigerant disposed therein; and

an oil collecting device that is configured such that after the existing refrigerant oil has been changed and before the refurbished air conditioner is run in a normal operating mode, the oil collecting device can draw in the replaced working refrigerant that is being circulated through the air conditioner and separate the existing refrigerant oil that is carried with the replaced working refrigerant,

the replaced working refrigerant being an HFC refrigerant containing at least 40 wt% of R32 that serves as a cleaning agent but contains no R134a refrigerant.

8. (Cancelled)

9. (Cancelled)

10. (Cancelled)